







THE PANELTEK PRODUCTS ADVANTAGE:

- Improved interlocking system that reduces moisture penetration.
- Uniquely designed panel with keyways that do not line up when properly installed
- Innovative panel using only Waterproof Glue and Exterior Grade thick 3/8" Plywood.
- Our staple-less panel eliminates rust stains from weathered staples.
- Installation up to 6-8 times faster than hand applied shingles.
- First Shingle panel with built-in expansion gap
- Exterior grade plywood core.

- Manufacturing & Finish is of the highest market quality.
- Flush bevel corners to match available.
- Scribed nailer guide on the panel.
- \$10 million product liability insurance coverage.
- 20 year warranty.
- Single course 8-foot panels.
- Custom design Keyway base lap in the joint.
- Minor bundled 8 panels.

W W W . P A N E L T E K P R O D U C T S . C O M

VERTICAL GRAIN SHINGLE Style **Butt Thickness** Size 1/2 inch 7-1/8" Even Butt 1/2 inch 7-1/8" Open Keyway 1/2 inch 5-5/16" **Even Butt** Open Keyway 1/2 inch 5-5/16"

PACKAGING			
	7-1/8"	160 panels per lift	21 panels/square
	5-5/16"	240 panels per lift	28 panels/square